



Fuse-link, high speed, 120 A, AC 690 V, DC 500 V, BS88, 37 x 94 mm, aR, BS

Catalog No. 120FEE

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	120
Rated voltage			AC 690 V DC 500 V
Construction size			BS88
Size			37 x 94 mm
Utilization category			aR
Breaking Capacity		kA	200
usable for size/applications			protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters
Standard/Approval			BS
Shape			offset bolted tags (dual barrel)
Standards/Regulations			BS88-4 IEC 60269-4
Optional accessories			fuse-holder BH-1132

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecI@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	120
Rated voltage		V	690
Voltage type			AC/DC
Rated switching capacity		kA	200
Utilization category			Other
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No

Assets (links)

Declaration of CE Conformity

00003218

Additional product information (links)

High-speed full-line catalogue (pdf)	http://www1.cooperbusssmann.com/pdf/dc416ece-4392-4b42-ab36-39df6058b353.pdf
--------------------------------------	---