

Catalog No. BB1P100M57

Delivery program

Product range			Fuse accessory
Basic function			BUSBAR
Field of application			low voltage
Functionality			can be cut to length
Rated current	I	A	100
Rated voltage			AC 600 V DC 1000 V
Size			15 x 16 x 1012 mm
Description			single phase 57-way comb-type busbar without end stop
Number of poles			57P
Standard/Approval			UL
Standards/Regulations			UL 508

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecI@ss10.0.1-27-37-13-06 [ACN992011])			
Number of phases			1
Number of poles			57
Suitable for number of devices			57
Pitch dimensions		mm	17.8
Cross section		mm ²	25
Length		mm	1012
Number of modular spacings			57
Rated permanent current I _u		A	100
Type of electric connection			Fork
Insulated			Yes
Rated surge voltage		kV	
Conditioned rated short-circuit current I _q		kA	10
Max. rated operation voltage U _e		V	600
Rated short-time withstand current I _{cw}		kA	10
Suitable for devices with N-busbar			No
Suitable for devices with auxiliary switch			No

Additional product information (links)

Product catalogue(pdf)	http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-literature/BUS_Ele_BR_3185_MFH.pdf
------------------------	---