



Fuse-link, LV, 125 A, AC 400 V, 22 x 58 mm, gL/gG, IEC

Catalog No. C22G125

EL-Nummer  
(Norway) 0001664190

## Delivery program

|                              |   |   |                                                        |
|------------------------------|---|---|--------------------------------------------------------|
| Product range                |   |   | Fuse                                                   |
| Basic function               |   |   | Fuse-link                                              |
| Field of application         |   |   | low voltage                                            |
| Rated current                | I | A | 125                                                    |
| Rated voltage                |   |   | AC 400 V                                               |
| Size                         |   |   | 22 x 58 mm                                             |
| Utilization category         |   |   | gL/gG                                                  |
| usable for size/applications |   |   | for industrial applications<br>for general purpose use |
| Standard/Approval            |   |   | IEC                                                    |
| Shape                        |   |   | cylindrical                                            |
| Standards/Regulations        |   |   | IEC 60269-2                                            |

## Technical data ETIM 7.0

|                                                                                                                                                                                               |  |    |                                               |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|-----------------------------------------------|
| Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)                                                                                                                           |  |    |                                               |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013]) |  |    |                                               |
| Size                                                                                                                                                                                          |  |    | 22x58 mm                                      |
| Rated voltage                                                                                                                                                                                 |  | V  | 400 - 400                                     |
| Rated voltage                                                                                                                                                                                 |  |    | Other                                         |
| Voltage type                                                                                                                                                                                  |  |    | AC                                            |
| Utilization category                                                                                                                                                                          |  |    | gL/gG (cable protection/equipment protection) |
| Rated operating frequency                                                                                                                                                                     |  | Hz | 45 - 62                                       |
| Nominal current                                                                                                                                                                               |  | A  | 125                                           |
| With striker                                                                                                                                                                                  |  |    | No                                            |
| Release characteristic                                                                                                                                                                        |  |    | Other                                         |
| Breaking capacity                                                                                                                                                                             |  | kA | 120                                           |

## Assets (links)

Declaration of CE Conformity

00003176

## Additional product information (links)

|                         |                                                                                                                                                                                                                                                                                                       |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product datasheet (PDF) | <a href="http://www.cooperindustries.com/content/dam/public/bussmann/iec-electrical/resources/data-sheets/bus-iec-ds-720115-cylindricalfuselinks.pdf">http://www.cooperindustries.com/content/dam/public/bussmann/iec-electrical/resources/data-sheets/bus-iec-ds-720115-cylindricalfuselinks.pdf</a> |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|