



Fuse-link, high speed, 315 A, DC 1000 V, 2XL, gPV, UL, IEC

Catalog No. PV-315A-2XL

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	315
Rated voltage			DC 1000 V
Construction size			2XL
Utilization category			gPV
Breaking Capacity		kA	33
usable for size/applications			photovoltaic array combiners and disconnects
Standard/Approval			UL IEC
Shape			square body with knife blade contacts
Standards/Regulations			IEC 60269-6 UL 2579
Optional accessories			SD2XL-S fuse holder and 170H0236 or 170H0238 microswitches

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	315
Rated voltage		V	1000
Voltage type			DC
Rated switching capacity		kA	33
Utilization category			gPV (photovoltaic protection)
Type of fuse status indicator			Top fuse status indicator
Insulated metal gripping lugs (IMGL)			No

Assets (links)

[Declaration of CE Conformity](#)
00003223

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbusmann.com/pdf/6788cf8f-aec7-45cd-9c42-10fe194c8f80.pdf
-------------------------	---